

LETTER OF AUTHORIZATION APPLICATION

AMENDMENT WEST 1

BOEM control number: T24-006

Requested period of effectiveness:

Start date: December 1st, 2024

End date: November 30th, 2025

A- Type of Survey

Please indicate which type of survey will be used in the proposed activity

Deep penetration seismic (greater than 1,500cuin total airgun array volume)

- 2D seismic-towed steamer
- 2D seismic-seafloor cable or nodes
- 3D seismic-towed steamer
- 3D seismic-seafloor cable or nodes
- NAZ
- WAZ
- 4D (time lapse)
- Vertical cable
- Borehole seismic (VSP)

Shallow penetration seismic (less than 1,500cuin total airgun array volume)

- Surface vessel
- Surface vessel and AUV/ROV
- Borehole seismic (VSP)

HRG surveys (no airgun used)

- Surface vessel
- AUV/ROV
- Both

Other

Describe (if other):

B Survey area and operational plan

Question:	Response:
Location:	East Breaks

(lease block, facility or prospect name, lat/lon, etc.)	
Overall duration of the activity: (days from mobilization to demobilization):	150 days
Areal extend of the survey area: (in OCS lease blocks or Km ² (Attach GIS file of the survey lines and/or survey area perimeter)	~453 OCS blocks – 10,629 Km ² Shape file attached separately.
Water depth range:	1,200 - 2,000 m
G&G ITR / PIES modeling zone(s) in which the activity will occur (1-7):	89.1 days in zone 6.
Number of days during the overall activity period on which the sound sources listed in section C will operate:	89.1 days

C Sound sources

List the same sound sources provided in response to question #3 in “Section D Proprietary Information Attachment” to the G&G Permit Application and indicate their Duration of Use.

The source types to be used during this survey will be Gemini 8000 in³. Gemini airgun arrays will be used for the entire survey and will fire using “flip-flap-flop” method with 2.5 second dithers applied to each source. The source firing sequence will create a 50m x 100 m shot grid. A separation distance of no less than 2000 m will be maintained between each source vessel.

Energy Source	Manu- facturer	Model	Total Array Volume & Number of Elements (cubic inches or Liters.)	Source Level (SL) in dB re 1µPa@1m in water (RMS)	Source Level (SL) in dB re 1µPa@1m in water (Peak to Peak)	Operating Frequency (Hz, kHz, range)	Pulse Duration (seconds, milli- seconds)	Pulse Rate (or Cycle) (Pulses per second or minute)	Towing Depth of the Source (ft or m)	Towing Depth of the Receiver(s) (ft or m)	Duration of Use (Number of Days or Percent of Active Sound Source Days)
PIES (Pressure Inverted Echo Sounder)	Sonardyne	8302-3116	N/A	190-202 dB	80-120 dB	14-19 kHz	N/A	1 pulse every 10 minutes	Placed on seabed	Placed on seabed	120 days
Extended Frequency Source	TGS	Gemini	8000 in ³	~220 dB	~243 dB	0-100 Hz		24 pulse / minute	8 m	OBN receivers on seabed	89.1 days

D Mitigation and monitoring effort

Question:	Response:
Please indicate which set of monitoring and mitigation measures from the ITR apply to the planned activity:	All monitoring and mitigation measures in the ITRs applicable to Airgun Surveys with a total volume >1,500 in ³ (Deep Penetration) will be followed.
Confirm that you will apply this set of monitoring and mitigation measures during the activity:	Yes

E Map of the survey and transit route:

